

# KOLLEZI

○ WALL



[WWW.KOLLEZI.COM](http://WWW.KOLLEZI.COM)

## Technical Information

\*Valid valve and rough-in position before installation

In-wall conceal tank.....Metal frame  
 Bearing capacity.....400 kg | 880 lb  
 Residential installation.....2" x4" & 6" stud wall  
 Flush type.....Dual flush  
 Water consumption.....0.8/1.6 GPF | 3/6 LPF  
 Flush action.....Gravity flush down  
 Outlet pipe.....Ø 4" | 100 mm  
 Inlet pipe.....Ø 2" | 50mm  
 Rough-in.....In-wall floor  
 Mounting holes.....7-9" | 180-230 mm  
 Dual flush button K4117.....Included  
 Warranty.....5 years  
 All product dimensions are nominal

## Information Technique

\*Valider la position de la valve d'alimentation et la plomberie brute avant l'installation

Système de réservoir mural.....Cadre de métal  
 Capacité portante.....400 kg | 880 lb  
 Installation résidentielle.....2" x4" & 6" Colomage  
 Type de chasse .....Double chasse  
 Consommation d'eau.....0.8/1.6 GPF | 3/6 LPF  
 Fonction de chasse.....Gravité directe  
 Tuyau de décharge.....Ø 4" | 100 mm  
 Tuyau d'entrée .....Ø 2" | 50 mm  
 Installation/plomberie brute.....Plancher mural  
 Trous d'installation.....7-9" | 180-230 mm  
 Bouton de chasse duo K4117.....Inclus  
 Garantie.....5 ans  
 Toutes les dimensions sont nominales

